



Information

Saab 9-3 Aero XWD / Turbo X

Technical Specifications

Engine:

2792cc. V6. Aluminum cylinder heads and block. Twin-scroll turbocharger, intercooled. DOHC, 24-valve. Variable valve timing (inlet). Dual-mass flywheel. Bosch Motronic ECM

Bore/stroke: 89.0/74.8 mm. Compression ratio: 9.5: 1. Max. Boost Pressure: 0.8 bar.

Max power: 280 hp (206 kW) @ 5,500 rpm.

Max. torque: 400 Nm @ 2,150 - 4,500 rpm

Transmission:

Saab XWD, all-wheel-drive.

6-speed manual or automatic gearbox

Electronic rear limited-slip differential (eLSD) standard with Turbo X

Suspension:

Front: MacPherson struts, gas shock absorbers. Anti-roll bar.



Aero XWD: 17 x 7", 225/50R17, 18 x 7.5", 235/45R18 optional

Turbo X : 18 x 7.5", 235/45R18, 19 x 8", 235/45R19 optional

Brakes:

Hydraulic, dual circuit, vacuum booster.

Ventilated discs. Aero XWD: 314 mm/ 292 mm, Turbo X: 345 mm / 292 mm

Performance Data (manual transmission)

0 - 100 kph:	Aero XWD: 6.2 s (Sport Sedan, 6.5 s (SportCombi) Turbo X : 5.7 s (Sport Sedan), 5.9 s (SportCombi)
80 - 120 kph (5 th gear):	Aero XWD: 7.9 s (Sport Sedan), 8.3 s (SportCombi) Turbo X : 7.9 s (Sport Sedan), 8.3 s (SportCombi)
Top Speed:	Aero XWD: 250 kph (Sport Sedan, SportCombi): Turbo X : 250 kph (Sport Sedan, SportCombi)
Fuel consumption/CO2:	Aero XWD, Turbo X: 10.7 / 254 g/km (Sport Sedan)
(combined, L/100km):	Aero XWD, Turbo X: 10.8 / 258 g/km (SportCombi)

#