



LAMPHOLDER W2 X 4.6D, WITHOUT LAMP,  
WITH HOLDER

### Mechanical design:

|                                                         |  |               |
|---------------------------------------------------------|--|---------------|
| product designation                                     |  | lampholder    |
| Number of NC contacts / for auxiliary contacts          |  | 0             |
| Number of NO contacts / for auxiliary contacts          |  | 0             |
| Number of change-over switches / for auxiliary contacts |  | 0             |
| Number of lampholders                                   |  | 1             |
| Execution of the mounting                               |  | W2 x 4.6d     |
| Product component / fluorescent materials               |  | No            |
| Design of the electrical connection                     |  | tab terminals |

### General technical details:

|                                            |   |          |
|--------------------------------------------|---|----------|
| Type of voltage / of the operating voltage |   | AC/DC    |
| Operating voltage                          |   |          |
| • at 50 Hz / at AC                         |   |          |
| • rated value                              | V | 5 ... 60 |
| • at 60 Hz / at AC                         |   |          |
| • rated value                              | V | 5 ... 60 |
| • for DC                                   |   |          |
| • rated value                              | V | 5 ... 60 |
| Operating current                          |   |          |
| • at AC-15 / at 230 V                      |   |          |

|                                                                                             |    |                   |
|---------------------------------------------------------------------------------------------|----|-------------------|
| • at 50 Hz / rated value                                                                    | A  | 4                 |
| • at DC-13 / at 24 V / rated value                                                          | A  | 3                 |
| Resistance against shock / for devices with incandescent lamp / according to IEC 60068-2-27 |    | <= 30g            |
| Resistance against vibration / according to IEC 60068-2-6                                   |    | 20 ... 200 Hz: 5g |
| Item designation / according to DIN EN 61346-2                                              |    | P                 |
| Item designation / according to DIN 40719 extendable after IEC 204-2 / according to IEC 750 |    | H                 |
| Ambient temperature                                                                         |    |                   |
| • during operating                                                                          | °C | -25 ... +60       |
| • during storage                                                                            | °C | -40 ... +80       |
| Protection class IP / of the terminal                                                       |    | IP00              |
| protection class IP / of the housing                                                        |    | IP00              |
| Type of mounting                                                                            |    | front mounting    |
| Width                                                                                       | mm | 19                |
| Height                                                                                      | mm | 19                |
| Depth                                                                                       | mm | 46                |

#### Certificates/approvals:

General Product Approval

other



CCC



CSA



GOST



UL

[Confirmation](#)

#### Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

Cax online generator:

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB2304-2A/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3SB2304-2A](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB2304-2A)

last change:

Feb 7, 2012